

6x6x10 Gas Oven Spec List

Overall exterior dimension with burner chamber, burner module, and control panel: 7ft (W) x 7ft (H) x 12ft (L)

Exterior unit dimension: 6ft (W) x 6ft (H) x 10ft (L)

Interior dimension: 64-inches (W) x 68-inches (H) x 112-inches (L)

Frame material: 16GA welded steel

Inside/outside metal: Premium G90 sheeting (18GA & 20GA)

Wall thickness: 4-inches

Insulation type: 2200-degree mineral wool (R15 batt)

Floor: Interior mounted 16GA G90 sheet

Weight: 2,750

Power requirement: 115-volt, 20 amp

Power source: NEMA 5/20P

Burner model: P250-LP/NG

Burner BTU rating: 50,000 min/250,000 max btu/h

Gas source: Liquid propane or natural gas

Ignition: 7300 vac direct spark

Burner CSA Certification: 189810-1154925

Burner UL Listed: Yes

Burner purge: On module/factory purge (30-second delay)

Doors: Single 6x6 (\$1,000 for 3x6 double door option)

Door latch system: One overhead explosion vent latch (180lb spring)

Circulation fan(s): 2 @ 260 CFM/Motion flow vented

Circulation fan HP: 1/15

Exhaust: 6-inch start collar w/o dampener

Exhaust type: Powered exhaust @129 CFM

Door seal: 550-degree silicone sponge

Unit max temperature: 550-degrees

PID model: SYL-2342AI

Warranty: 18-months parts, burner, and panel

Lead time: 2 weeks, expedited available (7-10 days @ \$2,500 cost)